

Zero-Gravity® Floor Unit The Suspended Radiation Protection System

Product Highlights:

Orthopedic Protection

Zero-Gravity[®] is designed to take the weight off of clinicians' bodies and to prevent fatigue and orthopedic strain, unlike conventional lead aprons.

Higher Radiation Protection

Zero-Gravity[®] provides superior operator protection during fluoroscopy compared to conventional lead aprons with undertable shields or ceiling mounted shields.^{1, 2, 3}

Flexibility

The Floor Unit can be easily re-positioned for a broad range of procedures and room configurations. Clinicians maintain patient access on both sides of the table.

Ease of Movement

Zero-Gravity[®] allows clinicians freedom of movement, especially during challenging procedures.



Model

Floor Unit - ZGM-6-5H

Description	ѕки
Zero-Gravity [®] Drape	ZGD20WA-Loop
Zero-Gravity [®] Vest, Small	ZGAV-S
Zero-Gravity [®] Vest, Medium	ZGAV-M
Zero-Gravity [®] Vest, Large	ZGAV-L

The Vest is also available in sizes XS, XL, 3XL.

1 Haussen DC, Van Der Born IMJ, Nogueira RG. J NeuroIntervent Surg 2016; 8:1052-1055.

2 Marichal DA, Anwar T, Kirsch D, et al. Comparison of a for radiation exposure of a simulated interventionalist. J Vasc Interv Radiol 2011; 22: 437--42.

3 Savage C, Seale IV TM, Shaw CJ et al. (2013) Evaluation of a Suspended Personal Radiation Protection System vs. Conventional Apron and Shields in Clinical Interventional Procedures, Open Journal of Radiology, http://dx.doi.org/10.4236/ojrad.2013.33024.

Zero-Gravity[®] Floor Unit



General Information		
A) Boom arm length	200 cm	
B) Balancer working length	106 cm	
C) Floor base dimensions	Width 122 cm; depth 71 cm	
D) Height	Max 274 cm; min 239 cm	
E) Overhead arm rotation	150°	
Floor Unit weight	341 kg	
Dimension of the wooden packaging (L $ imes$ W $ imes$ H)	112 cm x 150 cm x 224 cm	
Weight with packaging	636 kg	

Radiation Absorption		
Leaded head shield	0.5 mm Pb equivalency	
Leaded shoulder/body shield	1.00 mm Pb equivalency	

Measurements are approximations and subject to change by the manufacturer.

